



# CLEAN LIGHTWEIGHT SEAMLESS

## Walls and Ceilings

The need for a “clean” environment is met with Utilite easy-to-maintain interlocking wall panels. These versatile panels can be installed quickly, both vertically or horizontally, directly to stud or substrate.

## Features and Benefits

Clean, smooth white surface.

Innovative corrugated plastic core provides a lightweight, durable panel.

100% moisture resistant. Will not rot or corrode and is ideal for high water exposure areas.

Interlocking edge provides a near seamless appearance while reducing installation time.



# NUDO<sup>®</sup>

# PHYSICAL CHARACTERISTICS & PROPERTIES

## Standard Sizes

16" x 8'	24" x 8'
16" x 10'	24" x 10'
16" x 12'	24" x 12'
16" x 16'	24" x 16'
16" x 20'	24" x 20'



## Fire-Rating: Class A

Nominal 0.400" Thickness

## Certifications

Meets LA County Requirements for walls and ceilings  
 Meets USDA Requirements for walls and ceilings  
 Meets FDA Requirements for walls and ceilings  
 CFIA - ULCS 102.2 - Class A



## Physical Properties

Typical Value	Unit	Test Method	Property
Surface Burn Test	Class A	NFPA / IBC	ASTM E84
Flexural Strength	2,233	lbf / in <sup>2</sup>	ASTM C393
Flexural Modulus	156,976	psi	ASTM C393
Flexural Load	10,496	psi	ASTM D3043
Tensile Strength	1,308	psi	ASTM D638
Izod Impact	1.57	ft-lbs / in	ASTM D256